



- Cordless operation
- Wand tilt
- Smooth or embossed slat finish
- Snow White color
- 3" Crown valance included
- Optional cloth tapes
- Optional motorization
- 2-on-1 or 3-on-1 available for larger blinds

Specifications:

- | | |
|----------------------------------|--|
| 1. HEADRAIL: | 1.5" High x 2" Wide low profile PVC |
| 2. BOTTOMRAIL: | Rectangular, hollow PVC bottomrail with end caps |
| 3. SLATS: | 2" Wide Faux Wood PVC |
| 4. VALANCE: | 3" crown profile valance. Flush installation or returns provided. Clips are concealed behind valance. |
| 5. WAND TILTER: | The tilt wand is electro zinc coated solid steel measuring 1/4 inch at its widest points. The tilter wheel is made of acetal thermoplastic and the gear and housing are made of steel to provide smooth, quiet operation. |
| 6. CORDLESS: | Cordless design with a simple raise and lower by grasping the bottomrail. Incorporates a "crash proof" safety feature that locks blind automatically upon release of bottomrail. |
| 7. CORD LADDER: | Poylester braided cord ladders provide maximum strength and flexibility with minimum stretch ensuring the slats overlap correctly when in the closed position. Standard ladder spacing between slats is 44mm/1.73in. |
| 8. INSTALLATION BRACKETS: | Brackets are made of steel and color matched to the headrail. The front is hinged to lock the headrail in place. For blinds over 60" wide a center bracket will be provided. Extension and hold down brackets are available at no charge when requested. |